

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2020/878 - Europe

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : Hempadur 85675 Base  
Product identity : 8567511150  
Product type : epoxy phenolic paint (base for multi-component product)

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Field of application : metal industry, ships and shipyards.  
Ready-for-use mixture : 85671 = 85675 8.8 vol. / 97371 1.2 vol.  
Identified uses : Industrial applications, Used by spraying.

#### 1.3 Details of the supplier of the safety data sheet

Company details : HEMPEL A/S  
Lundtoftegårdsvej 91  
DK-2800 Kgs. Lyngby  
Denmark  
Tel.: + 45 45 93 38 00  
hempel@hempel.com  
Date of issue : 21 November 2022  
Date of previous issue : 16 November 2021.

#### 1.4 Emergency telephone number

Emergency telephone number (with hours of operation)  
  
+45 45 93 38 00 (08.00 - 17.00)  
See section 4 First aid measures.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226 FLAMMABLE LIQUIDS  
Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION  
Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION  
Skin Sens. 1, H317 SKIN SENSITIZATION  
Aquatic Chronic 3, H412 AQUATIC HAZARD (LONG-TERM)

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms :



Signal word : Danger  
Hazard statements : H226 - Flammable liquid and vapor.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H318 - Causes serious eye damage.  
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements :

Prevention : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Hazardous ingredients :  Bisphenol F-(epichlorhydrin) epoxy resin MW =< 700  
2-methylpropan-1-ol

Supplemental label elements :  Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.  
Contains epoxy constituents. May produce an allergic reaction.

#### Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

### SECTION 2: Hazards identification

#### 2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
epi-phenol F-(epichlorhydrin) epoxy resin MW =< 700	REACH #: 01-2119454392-40 EC: 500-006-8 CAS: 28064-14-4	≥10 - <25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≥10 - ≤25	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315	[1] [2]
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7 Index: 022-006-00-2	≥3 - ≤5	Carc. 2, H351 (inhalation)	[1] [*]
2-methylpropan-1-ol	REACH #: 01-2119484609-23 EC: 201-148-0 CAS: 78-83-1 Index: 603-108-00-1	≥3 - ≤5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	[1]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1 - ≤3	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304	[1] [2]
toluene	REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3	≤0.3	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304	[1] [2]

ATE [Dermal] = 1100 mg/kg  
ATE [Inhalation (gases)] = 5000 ppm  
ATE [Inhalation (vapours)] = 11 mg/l  
See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit, see section 8.

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General :	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 112 and give immediate treatment (first aid).
Eye contact :	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention.
Inhalation :	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and get medical attention immediately.
Skin contact :	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion :	If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting unless directed to do so by medical personnel. Lower the head so that vomit will not re-enter the mouth and throat.

### SECTION 4: First aid measures

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

##### Potential acute health effects

Eye contact : Causes serious eye damage.  
Inhalation : No known significant effects or critical hazards.  
Skin contact : Causes skin irritation. May cause an allergic skin reaction.  
Ingestion : No known significant effects or critical hazards.

##### Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:  
pain  
watering  
redness  
Inhalation : No specific data.  
Skin contact : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur  
Ingestion : Adverse symptoms may include the following:  
stomach pains

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.  
Specific treatments : No specific treatment.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Extinguishing media : Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray.  
Not to be used: waterjet.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.  
Hazardous combustion products : Decomposition products may include the following materials: carbon oxides sulfur oxides metal oxide/oxides

#### 5.3 Advice for firefighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid all direct contact with the spilled material. Exclude sources of ignition and be aware of explosion hazard. Ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8. No action shall be taken involving any personal risk or without suitable training. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

#### 6.2 Environmental precautions

### SECTION 6: Accidental release measures

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material.

#### 6.3 Methods and materials for containment and cleaning up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilled product.

#### 6.4 Reference to other sections

See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should be used only in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. No sparking tools should be used. Contains epoxy constituents. Avoid all possible skin contact with epoxy and amine containing products, they may cause allergic reactions.

Avoid inhalation of vapour, dust and spray mist. Avoid contact with skin and eyes. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Appropriate personal protective equipment: see Section 8. Always keep in containers made from the same material as the original one.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep out of the reach of children. Keep away from: Oxidizing agents, strong alkalis, strong acids. No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.

#### 7.3 Specific end use(s)

See separate Product Data Sheet for recommendations or industrial sector specific solutions.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Product/ingredient name	Exposure limit values
xylene	<b>EU OEL (Europe, 1/2022). [xylene, mixed isomers] Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 221 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. STEL: 442 mg/m <sup>3</sup> 15 minutes.
ethylbenzene	<b>EU OEL (Europe, 1/2022). Absorbed through skin.</b> STEL: 884 mg/m <sup>3</sup> 15 minutes. STEL: 200 ppm 15 minutes. TWA: 442 mg/m <sup>3</sup> 8 hours. TWA: 100 ppm 8 hours.
toluene	<b>EU OEL (Europe, 1/2022). Absorbed through skin.</b> TWA: 192 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours. STEL: 384 mg/m <sup>3</sup> 15 minutes. STEL: 100 ppm 15 minutes.

#### Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### SECTION 8: Exposure controls/personal protection

#### Derived effect levels

Product/ingredient name	Type	Exposure	Value	Population	Effects
bisphenol F-(epichlorhydrin) epoxy resin MW < 700	DNEL	Long term Dermal	104.15 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	29.39 mg/m <sup>3</sup>	Workers	Systemic
xylene	DNEL	Long term Inhalation	77 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic
ethylbenzene	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	77 mg/m <sup>3</sup>	Workers	Systemic
toluene	DNEL	Long term Dermal	384 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	192 mg/m <sup>3</sup>	Workers	Systemic

#### Predicted effect concentrations

Product/ingredient name	Compartment Detail	Value	Method Detail
bisphenol F-(epichlorhydrin) epoxy resin MW < 700	Fresh water	0.003 mg/l	-
	Marine water	0.0003 mg/l	-
	Sewage Treatment Plant	10 mg/l	-
	Fresh water sediment	0.294 mg/kg dwt	-
	Marine water sediment	0.0294 mg/kg dwt	-
xylene	Soil	0.237 mg/kg dwt	-
	Fresh water	0.327 mg/l	-
	Marine water	0.327 mg/l	-
	Fresh water sediment	12.46 mg/kg	-
	Marine water sediment	12.46 mg/kg	-
ethylbenzene	Soil	2.31 mg/kg	-
	Sewage Treatment Plant	6.68 mg/l	-
	Fresh water	0.1 mg/l	-
	Marine water	0.01 mg/l	-
	Sewage Treatment Plant	9.6 mg/l	-
toluene	Fresh water sediment	13.7 mg/kg	-
	Soil	2.68 mg/kg	-
	Fresh water	0.68 mg/l	-
	Marine water	0.68 mg/l	-
	Sewage Treatment Plant	13.61 mg/l	-
phenol	Fresh water sediment	16.39 mg/kg	-
	Marine water sediment	16.39 mg/kg	-
	Soil	2.89 mg/kg	-
	Fresh water	0.0077 mg/l	-
	Marine water	0.00077 mg/l	-
formaldehyde	Sewage Treatment Plant	2.1 mg/l	-
	Fresh water sediment	0.0915 mg/kg	-
	Marine water sediment	0.00915 mg/kg	-
	Soil	0.36 mg/kg	-
	Fresh water	0.47 mg/l	-
	Marine water	0.47 mg/l	-
	Fresh water sediment	2.44 mg/kg	-
Marine water sediment	2.44 mg/kg	-	
	Soil	0.29 mg/kg	-
	Sewage Treatment Plant	0.19 mg/l	-

#### 8.2 Exposure controls

##### Appropriate engineering controls

Arrange sufficient ventilation by local exhaust ventilation and good general ventilation to keep the airborne concentrations of vapors or dust lowest possible and below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

##### Individual protection measures

- General : Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. Safety eyewear should be used when there is a likelihood of exposure.
- Hygiene measures : Wash hands, forearms, and face thoroughly after handling compounds and before eating, smoking, using lavatory, and at the end of day.
- Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

### SECTION 8: Exposure controls/personal protection

Hand protection :	<p>Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training. The quality of the chemical-resistant protective gloves must be chosen as a function of the specific workplace concentrations and quantity of hazardous substances.</p> <p>Since the actual work situation is unknown. Supplier of gloves should be contacted in order to find the appropriate type. Below listed glove(s) should be regarded as generic advice:</p> <p>Recommended: Silver Shield / Barrier / 4H gloves, polyvinyl alcohol (PVA), Viton® May be used: nitrile rubber, butyl rubber Short term exposure: neoprene rubber, natural rubber (latex), polyvinyl chloride (PVC)</p>
Body protection :	<p>Personal protective equipment for the body should be selected based on the task being performed and the risks involved handling this product.</p> <p>Wear suitable protective clothing. Always wear protective clothing when spraying.</p>
Respiratory protection :	<p>Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If working areas have insufficient ventilation: When the product is applied by means that will not generate an aerosol such as, brush or roller wear half or totally covering mask equipped with gas filter of type A, when grinding use particle filter of type P. Be sure to use an approved/certified respirator or equivalent.</p>

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state :	Liquid.
Color :	Gray
Odor :	Solvent-like
pH :	Testing not relevant or not possible due to nature of the product.
Melting point/freezing point :	1580°C This is based on data for the following ingredient: barium sulphate
Boiling point/boiling range :	Testing not relevant or not possible due to nature of the product.
Flash point :	Closed cup: 23°C (73.4°F)
Evaporation rate :	Testing not relevant or not possible due to nature of the product.
Flammability :	Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.
Lower and upper explosive (flammable) limits :	0.8 - 10.9 vol %
Vapor pressure :	Testing not relevant or not possible due to nature of the product.
Vapor density :	Testing not relevant or not possible due to nature of the product.
Specific gravity :	1.765 g/cm <sup>3</sup>
Partition coefficient (LogKow) :	Testing not relevant or not possible due to nature of the product.
Auto-ignition temperature :	Lowest known value: 415°C (779°F) (2-methylpropan-1-ol).
Decomposition temperature :	Testing not relevant or not possible due to nature of the product.
Viscosity :	Aspiration hazard (H304) Not classified. Testing not relevant due to nature of the product.
Explosive properties :	<p>Explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and oxidizing materials.</p> <p>Slightly explosive in the presence of the following materials or conditions: reducing materials.</p>
Oxidizing properties :	Testing not relevant or not possible due to nature of the product.

#### 9.2 Other information

Solvent(s) % by weight :	Weighted average: 18 %
Water % by weight :	Weighted average: 0 %
VOC content :	310.9 g/l
VOC content, Ready-for-use mixture :	334.2 g/l
TOC Content :	Weighted average: 265 g/l

### SECTION 9: Physical and chemical properties

Solvent Gas : Weighted average: 0.077 m<sup>3</sup>/l

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

#### 10.2 Chemical stability

The product is stable.

#### 10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

#### 10.4 Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

#### 10.5 Incompatible materials

Highly reactive or incompatible with the following materials: oxidizing materials.

Reactive or incompatible with the following materials: reducing materials.

#### 10.6 Hazardous decomposition products

When exposed to high temperatures (i.e. in case of fire) harmful decomposition products may be formed:

Decomposition products may include the following materials: carbon oxides sulfur oxides metal oxide/oxides

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to component solvent vapor concentrations may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headaches, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Accidental swallowing may cause stomach pain. Chemical lung inflammation may occur if the product is taken into the lungs via vomiting.

Epoxy and amine containing products can cause skin disorders such as allergic eczema. The allergy may arise after only a short exposure period.

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
bisphenol F-(epichlorhydrin) epoxy resin MW =< 700	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
xylene	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours
	LC50 Inhalation Vapor	Rat	6350 ppm	4 hours
	LD50 Dermal	Rabbit	>4200 mg/kg	-
	LD50 Oral	Rat	3523 mg/kg	-
titanium dioxide	LC50 Inhalation Dusts and mists	Rat	>6.8 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
2-methylpropan-1-ol	LC50 Inhalation Vapor	Rat	19200 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	3400 mg/kg	-
	LD50 Oral	Rat	2460 mg/kg	-
ethylbenzene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
toluene	LC50 Inhalation Vapor	Rat	>20 mg/l	4 hours
	LD50 Oral	Rat	636 mg/kg	-

#### Acute toxicity estimates

**SECTION 11: Toxicological information**

Product/ingredient name	Oral mg/kg	Dermal mg/kg	Inhalation (gases) ppm	Inhalation (vapors) mg/l	Inhalation (dusts and mists) mg/l
Hempadur 85675 Base		9783	44468	441.8	
xylene	3523	1100	5000		
2-methylpropan-1-ol	2460	3400			
ethylbenzene	3500			11	

**Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure
bisphenol F-(epichlorhydrin) epoxy resin MW =< 700	Eyes - Mild irritant	Rabbit	-	-
	Skin - Mild irritant	Rabbit	-	-
xylene	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams
	Skin - Irritant	Rabbit	-	-
titanium dioxide	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams
	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent
2-methylpropan-1-ol	Eyes - Irritant	Rabbit	-	-
	Skin - Irritant	Rabbit	-	-
ethylbenzene	Eyes - Mild irritant	Rabbit	-	-
	Respiratory - Mild irritant	Rabbit	-	-
toluene	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams
	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 milligrams
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams

**Sensitizer**

Product/ingredient name	Route of exposure	Species	Result
bisphenol F-(epichlorhydrin) epoxy resin MW =< 700	skin	Mouse	Sensitizing

**Mutagenic effects**

No known significant effects or critical hazards.

**Carcinogenicity**

No known significant effects or critical hazards.

**Reproductive toxicity**

No known significant effects or critical hazards.

**Teratogenic effects**

No known significant effects or critical hazards.

**Specific target organ toxicity (single exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
2-methylpropan-1-ol	Category 3		Respiratory tract irritation
toluene	Category 3		Narcotic effects
	Category 3		Narcotic effects

**Specific target organ toxicity (repeated exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs
toluene	Category 2	-	-

**Aspiration hazard**

Product/ingredient name	Result
ethylbenzene	ASPIRATION HAZARD - Category 1
toluene	ASPIRATION HAZARD - Category 1

**Information on the likely routes of exposure**

Routes of entry anticipated: Oral, Dermal, Inhalation.

**Potential chronic health effects**

Sensitization : Contains bisphenol F-(epichlorhydrin) epoxy resin MW =< 700. May produce an allergic reaction.

**11.2 Information on other hazards**

Endocrine disrupting properties : See Section 15 for details.



### SECTION 11: Toxicological information

Other information : No additional known significant effects or critical hazards.

### SECTION 12: Ecological information

#### 12.1 Toxicity

Do not allow to enter drains or watercourses. Harmful to aquatic life with long lasting effects.

Product/ingredient name	Result	Species	Exposure
bisphenol F-(epichlorhydrin) epoxy resin MW =< 700	Acute EC50 9.4 mg/l	Algae	72 hours
titanium dioxide	Acute EC50 1.7 mg/l	Daphnia	48 hours
	Acute LC50 1.5 mg/l	Fish	96 hours
2-methylpropan-1-ol	Acute LC50 >100 mg/l	Daphnia	48 hours
	Acute LC50 >100 mg/l	Fish	96 hours
ethylbenzene	Chronic NOEC 4000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
toluene	Chronic NOEC <1000 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Chronic NOEC <500000 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days

#### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
bisphenol F-(epichlorhydrin) epoxy resin MW =< 700	-	10 - 16 % - Not readily - 28 days	-	-
xylene	OECD 301F Ready Biodegradability - Manometric Respirometry Test	90 - 98 % - Readily - 28 days	-	-
ethylbenzene	-	>60 % - Readily - 28 days	-	-
toluene	-	>70 % - Readily - 28 days	-	-
	-	100 % - Readily - 14 days	-	-

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bisphenol F-(epichlorhydrin) epoxy resin MW =< 700	-	10 - 16%; 28 day(s)	Not readily
xylene	-	-	Readily
ethylbenzene	-	-	Readily
toluene	-	-	Readily

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
bisphenol F-(epichlorhydrin) epoxy resin MW =< 700	3.242	31	low
xylene	3.12	8.1 - 25.9	low
2-methylpropan-1-ol	1	-	low
ethylbenzene	3.6	-	low
toluene	2.73	90	low

#### 12.4 Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : No known data available in our database.

Mobility : No known data available in our database.

#### 12.5 Results of PBT and vPvB assessment

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
This mixture does not contain any substances that are assessed to be a PBT or a vPvB.							

#### 12.6 Endocrine disrupting properties

See Section 15 for details.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Residues of the product is listed as hazardous waste. Dispose of according to all state and local applicable regulations. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Spillage, remains, discarded clothes and similar should be discarded in a fireproof container.

European waste catalogue no. (EWC) is given below.




European waste catalogue (EWC) : 08 01 11\*

#### Packaging

The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

### SECTION 14: Transport information

Transport may take place according to national regulation or ADR for transport by road, RID for transport by train, IMDG for transport by sea, IATA for transport by air.

	14.1 UN / ID no.	14.2 Proper shipping name	14.3 Transport hazard class(es)	14.4 PG*	14.5 Env*	Additional information
<b>ADR/RID Class</b>	UN1263	PAINT	3 	III	No.	<b>Tunnel code</b> (D/E)
<b>IMDG Class</b>	UN1263	PAINT	3 	III	No.	<b>Emergency schedules</b> F-E, S-E
<b>IATA Class</b>	UN1263	PAINT	3 	III	No.	-

PG\* : Packing group

Env.\* : Environmental hazards

#### 14.6 Special precautions for user

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization - Substances of very high concern

##### Annex XIV

None of the components are listed.

##### Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

##### Other EU regulations

**Seveso category** This product is controlled under the Seveso III Directive.

##### Seveso category

P5c: Flammable liquids 2 and 3 not falling under P5a or P5b

#### 15.2 Chemical Safety Assessment

### SECTION 16: Other information

Abbreviations and acronyms :

ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 EUH statement = CLP-specific Hazard statement  
 RRN = REACH Registration Number  
 DNEL = Derived No Effect Level  
 PNEC = Predicted No Effect Concentration

Full text of abbreviated H statements :

H225 Highly flammable liquid and vapor.  
 H226 Flammable liquid and vapor.  
 H304 May be fatal if swallowed and enters airways.  
 H312 Harmful in contact with skin.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H351 Suspected of causing cancer.  
 H361d Suspected of damaging the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H411 Toxic to aquatic life with long lasting effects.  
 H412 Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS] :

Acute Tox. 4 ACUTE TOXICITY - Category 4  
 Aquatic Chronic 2 AQUATIC HAZARD (LONG-TERM) - Category 2  
 Aquatic Chronic 3 AQUATIC HAZARD (LONG-TERM) - Category 3  
 Asp. Tox. 1 ASPIRATION HAZARD - Category 1  
 Carc. 2 CARCINOGENICITY - Category 2  
 Eye Dam. 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 Eye Irrit. 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2  
 Flam. Liq. 2 FLAMMABLE LIQUIDS - Category 2  
 Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3  
 Repr. 2 TOXIC TO REPRODUCTION - Category 2  
 Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2  
 Skin Sens. 1 SKIN SENSITIZATION - Category 1  
 Skin Sens. 1B SKIN SENSITIZATION - Category 1B  
 STOT RE 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2  
 STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

**Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Classification	Justification
FLAMMABLE LIQUIDS SKIN CORROSION/IRRITATION SERIOUS EYE DAMAGE/ EYE IRRITATION SKIN SENSITIZATION AQUATIC HAZARD (LONG-TERM)	On basis of test data Calculation method Calculation method Calculation method Calculation method

**Notice to reader**

Indicates information that has changed from previously issued version.

The information contained in this safety data sheet is based on the present state of knowledge and EU and national legislation. It provides guidance on health, safety and environmental aspects for handling the product in a safe way and should not be construed as any guarantee of the technical performance or suitability for particular applications.

It is always the duty of the user/employer to ascertain that the work is planned and carried out in accordance with the national regulations.

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

### General description of the process covered

Indoor or outdoor spray painting by professionals or with brush, roller, putty knife, dipping etc. with good general room ventilation

**This safe use information is linked to** : Professional spray painting and/or low-energy painting, local effect - Level III  
Skin Corr. 1, Eye Dam. 1, Resp. Sens. 1 or EUH071

**Sector(s) of use** : Industrial uses - Professional uses

**Product category(ies)** : Coatings and paints, thinners, paint removers

### Operational conditions

**Place of use** : Indoor or outdoor use

### Risk management measures (RMM)

Contributing activity	Process category (ies)	Maximum duration	Ventilation		Respiratory	Eye	Hands
			Type	air changes per hour			
Preparation of material for application	PROC05	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.
Loading of application equipment and handling of coated parts before curing	PROC08a	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.
Professional application of coatings by brush or roller	PROC10	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.
Professional application of coatings by spraying	PROC11	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.
Film formation - force drying, stoving and other technologies	PROC04	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	None	Wear suitable gloves tested to EN374.
Cleaning	PROC05	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	Wear a respirator conforming to EN140 with an assigned protection factor of at least 10.	Use eye protection according to EN 166.	Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.
Waste management	PROC08a	More than 4 hours	Good general room ventilation - Outdoors	3 - 5	None	Use eye protection according to EN 166.	Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

See chapter 8 of this Safety Data Sheet for specifications.

